METEOR EO Mapping of Exposure Report Number: WP4.2/P 1 December 2018





Contributors: M O.Hara









# Document Verification

Project	METEOR: Modelling Exposure Through Earth Observation Routines
Report Title	METEOR EO Mapping of Exposure
Related Milestone	
Reference as	HOT (2018) METEOR EO Mapping of Exposure. Report WP4.2/P
Release Type	Public / Confidential / Confidential with Embargo Period

Prepared by: Contributors				
Name(s):	Signature(s):	Date(s):		
Mhairi O'Hara		7 December 2018		
Approved by: Project Manager	1	1		
Name:	Signature:	Date:		
Kay B. Smith	Kay Smith	7 December 2018		
Approved by: UKSA IPP Project Officer				
Name:	Signature:	Date:		

Date	Version	Alterations	Editor





# Contents

DOCUMENT VERIFICATIONI		
ACRONY	MS	1
1. INTE	RODUCTION	3
1.1.	PROJECT SUMMARY	3
1.2.	METEOR PROJECT OVERVIEW	3
1.3.	PROJECT OBJECTIVES	4
1.4.	Work Packages	4
1.5.	IN-SITU DATA INPUTS AND VALIDATION	5
2. OPE	NSTREETMAP	6
2.1.	WHAT IS IT?	6
2.2.	OPEN DATA	6
2.3.	DATA STRUCTURE	7
2.4.	WHY USE IT?	8
3. PAR	TICIPATORY MAPPING	9
4. REIV	IOTE DIGITISATION	10
4.1.	Overview	
4.2.	Tools	11
4.2.2	1. Tasking Manager	
4.2.2	2. iD Editor	
4.2.3	3. JOSM	
4.3.	IMAGERY	15
4.4.	QUALITY ASSURANCE	
5. KAT	HMANDU	
5.1.	Kathmandu Living Labs	
5.2.	Homogeneous Zones	
5.3.	TASKING MANAGER PROJECTS	20
5.4.	IMAGERY	21
5.5.	STATISTICS	
5.6.	DATASETS	24
6. DAR	ES SALAAM	27
6.1.	Ramani Huria	27
6.2.	Homogeneous Zones	





6	.3.	TASKING MANAGER PROJECTS	. 29
6	.4.	IMAGERY	.31
6	.5.	STATISTICS	. 33
6	.6.	DATASETS	. 35
7.	CON	CLUSION	.38
APP	ENDI	(1	.39
Р	re Dig	ITISATION	. 39
Р	OST DI	GITISATION	.41

## Figures

Figure 1: GFDRR Challenge Fund HEV-E Data Platform	5
Figure 2: HOT Tasking Manager	11
Figure 3: iD Editor	12
Figure 4: JOSM	14
Figure 5: OpenAerialMap	16
Figure 6: JOSM Validation Tool	17
Figure 7: Kathmandu Homogeneous Zones	19
Figure 8: Kathmandu Tasking Manager Project	21
Figure 9: Digitised Buildings over Imagery in Bhaktapur Dense Residential Zone	22
Figure 10: Kathmandu Dense Residential Zone	25
Figure 11: Kathmandu Industrial Zone	25
Figure 12: Kathmandu Informal Zone	26
Figure 13: Kathmandu New industrial Zone	26
Figure 14: Kathmandu Urban Zone	27
Figure 15: Dar es Salaam Homogeneous Zones	28
Figure 16: Dar es Salaam Tasking Manager Project	30
Figure 17: Satellite Imagery, Dar es Salaam Industrial Zone	32
Figure 18: Satellite Imagery with Digitised Buildings, Dar es Salaam Industrial Zone	32
Figure 19: Dar es Salaam OpenStreetMap Buildings Pre Digitisation	34
Figure 20: OpenStreetMap Buildings Post Digitisation, Dar es Salaam	34
Figure 21: Dar es Salaam High Urban Development Zone	35





Figure 22: Dar es Salaam Industrial Development Zone	36
Figure 23: Dar es Salaam Rural Settlement Zone	36
Figure 24: Dar es Salaam Single Family Residential Zone	37
Figure 25: Dar es Salaam Urban Development Zone	37
Figure 26: Kathmandu Living Labs Digitisation Team	38
Figure 27: Ramani Huria Digitisation Team	38

## Tables

Table 1: METEOR Project Summary	.3
Table 2: Overview of METEOR Work Packages	.5
Table 3: Overview of HOT Work Packages	.6
Table 4: Tasking Manager References	12
Table 5: iD Editor References	13
Table 6: JOSM References	15
Table 7: Aerial Imagery Resources	16
Table 8: Quality Assurance Resources	17
Table 9: Kathmandu Homogeneous Zones	19
Table 10: Kathmandu Tasking Manager Project	21
Table 11: Kathmandu Imagery Specifications	22
Table 12: Kathmandu Buildings Count Pre and Post Digitisation	23
Table 13: Kathmandu Building Quality Pre and Post Digitisation	24
Table 14: Dar es Salaam Homogeneous Zones	29
Table 15: Dar es Salaam Tasking Manager Projects	31
Table 16: Dar es Salaam Imagery Specifications	31
Table 17: Dar es Salaam Building Count Pre and Post Digitisation	33





# Acronyms

Acronym	Full Text	Description
BGS	British Geological Survey	An organisation providing expert advice in all areas of geoscience to the UK government and internationally
DMD	Disaster Management Department	Prime Minister's Office of Tanzania focused on disaster risk
DRM	Disaster Risk Management	
DRR	Disaster Risk Reduction	
EO	Earth Observation	
FATHOM		Provides innovative flood modelling and analytics, based on extensive flood risk research
GEM	Global Earthquake Model	Non-profit organisation focused on the pursuit of earthquake resilience worldwide
НОТ	Humanitarian OpenStreetMap Team	A global non-profit organisation the uses collaborative technology to create OSM maps for areas affected by disasters
InaSAFE		Free open software that produces realistic natural hazard impact scenarios for better planning, preparedness and response activities
ImageCat		International risk management innovation company supporting the global risk and catastrophe management needs of the insurance industry, governments and NGOs
IPP	International Partnership Programme	
KLL	Kathmandu Living Labs	
Mapathon		Coordinated mapping event where individuals learn about OSM, and make edits to the map through remote digitising of satellite imagery
METEOR	Modelling Exposure Through Earth Observation Routines	
NGO	Non Government Organisation	





NSET	National Society for Earthquake Technology	Non-governmental organisation working on reducing earthquake risk in Nepal and abroad
ODA	Official Development Assistance	
ODbL	Open Database License	
ОРМ	Oxford Policy Management	Organisation focused on sustainable project design and implementation for reducing social and economic disadvantage in low-income countries
OSM	OpenStreetMap	A collaborative project to create a free and open editable map database of the world
QGIS		Free open source desktop geographic information system
Ramani Huria		A community mapping project based in Dar Es Salaam, Tanzania
UAV	Unmanned Aerial Vehicle	
UKSA	United Kingdom Space Agency	
WASH	Water, Sanitation and Hygiene	
WP	Work Package	





## 1. Introduction

## 1.1. Project Summary

Project Title	Modelling Exposure Through Earth Observation Routines (METEOR): EO- based Exposure, Nepal and Tanzania				
Starting Date	08/02/2018				
Duration	36 months				
Partners	UK Partners: The British Geological Survey (BGS) (Lead), Oxford Policy Management Limited (OPM), SSBN Limited International Partners: The Disaster Management Department, Office of the Prime Minister – Tanzania, The Global Earthquake Model (GEM) Foundation, The Humanitarian OpenStreetMap Team (HOT), ImageCat, National Society for Earthquake Technology (NSET) – Nepal				
Target Countries	Nepal and Tanzania for "level 2" results and all 47 Least Developed ODA countries for "level 1" data				
IPP Project	IPPC2_07_BGS_METEOR				

Table 1: METEOR Project Summary

## 1.2. METEOR Project Overview

At present, there is a poor understanding of population exposure in some Official Development Assistance (ODA) countries, which causes major challenges when making Disaster Risk Management decisions. Modelling Exposure Through Earth Observation Routines (METEOR) takes a step-change in the application of Earth Observation exposure data by developing and delivering more accurate levels of population exposure to natural hazards. Providing new consistent data to governments, town planners and insurance providers will promote welfare and economic development in these countries and better enable them to respond to the hazards when they do occur.

METEOR is funded through the second iterations of the UK Space Agency's (UKSA) International Partnership Programme (IPP), which uses space expertise to deliver innovative solutions to real world problems across the globe. The funding helps to build sustainable development while building effective partnerships that can lead to growth opportunities for British companies.





## 1.3. Project Objectives

METEOR aims to formulate an innovative methodology of creating exposure data through the use of EO-based imagery to identify development patterns throughout a country. Stratified sampling technique harnessing traditional land use interpretation methods modified to characterise building patterns can be combined with EO and in-field building characteristics to capture the distribution of building types. These protocols and standards will be developed for broad application to ODA countries and will be tested and validated for both Nepal and Tanzania to assure they are fit-for-purpose.

Detailed building data collected on the ground for the cities of Kathmandu and Dar es Salaam will be used to compare and validate the EO generated exposure datasets. Objectives of the project look to deliver exposure data or 48 of the least developed ODA countries, including Nepal and Tanzania. Create open protocols to develop critical exposure information from EO data and capacity-building of local decision makers to apply data and assess hazard exposure. The eight work packages (WP) that make up the METEOR project are outlined below in section 1.4.

## 1.4. Work Packages

Outlined below are the eight work packages (WP) that make up the METEOR project. These are lead by various partners with a brief description of what each of the work packages cover. HOT is leading WP.4 Inputs and Validation, which focuses on the collection of exposure data in Kathmandu in Nepal and Dar es Salaam in Tanzania (**Error! Reference source not found.**). This data will assist with the validation and calibration of national exposure datasets created through the classification of building patterns from satellite imagery carried out by ImageCat in WP.3.

Work Package	Title	Lead	Overview
WP1	Project Management	BGS	Project management, meetings with UKSA, quarterly reporting and the provision of feedback on project deliverables and direction across primary stakeholders.
WP2	Monitoring and Evaluation	ОРМ	Monitoring and evaluation of the project and its impact, using a theory of change approach to assess whether the associated activities are leading to the desired outcome.
WP3	EO Data for Exposure Development	ImageCat	EO-based data for exposure development, methods and protocols of segmenting/classifying building patterns for stratified sampling of building characteristics.
WP4	Inputs and Validation	НОТ	Collect exposure data in Kathmandu and Dar es Salaam to help validate and calibrate the data derived from the classification of building patterns from EO-based imagery.
WP5	Vulnerability and Uncertainty	GEM	Investigate how assumptions, limitations, scale and accuracy of exposure data, as well as decisions in data development process lead to modelled uncertainty.





WP6	Multiple Hazard Impact	BGS	Multiple hazard impacts on exposure and how they may be addressed in disaster risk management by a range of stakeholders
WP7	Knowledge Sharing	GEM	Disseminate to the wider space and development sectors through dedicated web-portals and use of the Challenge Fund open databases.
WP8	Sustainability and Capacity-Building	ImageCat	Sustainability and capacity-building, with the launch of the databases for Nepal and Tanzania while working with in- country experts.

Table 2: Overview of METEOR Work Packages



Figure 1: GFDRR Challenge Fund HEV-E Data Platform

## 1.5. In-Situ Data Inputs and Validation

The project WP led by HOT is broken down into six deliverables, which are focused on the mapping of exposure data for the cities of Kathmandu and Dar es Salaam in OpenStreetMap (OSM). These involve importing existing data into OSM, the remote mapping of building footprints and road networks, drafting protocols for crowdsourcing exposure data, collecting detailed attribute information on the ground and producing a final report (Table 3).





Work	Title	Overview
Package		
WP4.1	Import Existing Data into OSM	Review and assess the suitability of existing open datasets for import into OSM for Kathmandu and Dar es Salaam
WP4.2	EO Mapping of Exposure Data	Remote mapping of building footprints and road networks in OSM for Kathmandu and Dar es Salaam
WP4.3	Protocols for Crowdsourcing Exposure Data	Draft protocols for the crowdsourcing of exposure data in OSM, covering data imports, remote mapping and ground data collection
WP4.4	Ground Data Collection using Protocols I	Collect exposure data on the ground for Kathmandu using a data model developed in line with the requirements for WP.3
WP4.5	Ground Data Collection using Protocols II	Collect exposure data on the ground for Dar es Salaam using a data model developed in line with the requirements for WP.3
WP4.6	Final Report	Deliver a final version of WP.4.3 along with the resulting data from WP.4.4. and WP.4.5

Table 3: Overview of HOT Work Packages

## 2. OpenStreetMap

#### 2.1. What is it?

OSM is a crowdsourced geospatial database of the world built largely by volunteers and professionals digitising aerial imagery, collecting attribute information on the ground and liberating existing public sources of geospatial data. Known as the 'Wikipedia' of maps, the data is freely accessible to all under the Open Database License (ODbL)<sup>1</sup>, meaning that it can be queried, used, manipulated, contributed to and redistributed in any form. OSM is the ideal database for humanitarian efforts and disaster management, as it is a great source of geographic baseline data for many cities around the globe, especially in countries with emerging economies that are not always on the map.

## 2.2. Open Data

The ODbL license is a copyleft ("share alike") agreement intended to allow users to freely share, modify, and use a database while maintaining this same freedom for others.

Published by Open Data Commons, part of the Open Knowledge Foundation2, the ODbL license enables OSM to be a source of powerful geospatial data to make change, particularly in ODA countries where a potential lack of internal funds and skill sets make it difficult to create up-to-date exposure data themselves. Such data is necessary to conduct hazard impact risk assessments and carry out informed appropriate disaster management decisions. One project may focus on creating data in OSM

<sup>&</sup>lt;sup>1</sup> https://opendatacommons.org/licenses/odbl/

<sup>&</sup>lt;sup>2</sup> https://okfn.org/





for a specific purpose, but this data can then be used by anyone for their area of interest. This freedom of use is outlined on the ODbL website (Open Data Commons, 2018):

#### You are free:

- To Share: To copy, distribute and use the database
- To Create: To produce works from the database
- To Adapt: To modify, transform and build upon the database

#### As long as you:

- Attribute: You must attribute any public use of the database, or works produced from the database, in the manner specified in the ODbL. For any use or redistribution of the database, or works produced from it, you must make clear to others the license of the database and keep intact any notices on the original database
- Share-Alike: If you publicly use any adapted version of this database, or works produced from an adapted database, you must also offer that adapted database under the ODbL
- Keep open: If you redistribute the database, or an adapted version of it, then you may use technological measures that restrict the work (such as DRM) as long as you also redistribute a version without such measures

#### 2.3. Data Structure

Geospatial data is stored in OSM as vectors, with three types of elements:

- 1. Nodes, which represent a point on the surface of the earth
- 2. Ways, which are sets of ordered nodes that can form lines or polygons
- 3. **Relations**, which are sets of nodes, ways and/or relations as members that are used to define logical or geographic relationships between other elements



Each of these elements can have any number of key=value tags, that represents the attribute information for a given figure. For example, a post office may be represented by a way with the tags building=yes and amenity=post\_office, to help identify the purpose of the building.





## 2.4. Why use it?

The most common question people ask is: *Why would you use OpenStreetMap if there is Google Maps?*<sup>3</sup> These platforms have many similarities and address the same basic human of spatially knowing where things are. In short, OSM represents an open approach to how data is collected and distributed, which makes it fast, free, flexible and widespread; an ideal combination for development application among others.

In the case of Haiti, the OSM community needed just a few hours to remotely digitise earthquake affected areas from satellite imagery, in contrast to commercial maps that had no way of responding in such a short period. The thousands of active volunteers around the globe are what made this possible, and the fact that every update is immediately visible to all other users, and is also version controlled. In many cases, the OSM community has been able to achieve even higher detail than any other map source.

The very idea behind OSM was to solve the problem of data restriction by using a Wikipedia model. Each edit made in OSM is owned by the community, whereas each change made in commercial map is owned by the providers. Data in commercial maps is copyrighted and so it can be subject to licensing fees and contractual restrictions. OSM is, and always will be, available for free. This open access to geospatial data makes it easy for researchers, governments, disaster management agencies and policy implementers to work collectively from the same database.

OSM is also ready for any kind of operation. Many major organisations are choosing OSM for their maps because it allows for customization based on need. It has been used to collect functioning and nonfunctioning water facilities in northern Uganda, to mapping hundreds of thousands of shelters in Bangladesh, to planning logistics for a Yellow Fever campaign in the Democratic Republic of Congo and mapping the exposure information of infrastructure for hazard impact. It allows access to all of the map offline and can be formatted in local languages, transcending national boundaries.

Most importantly, OSM emphasizes local knowledge across the globe. The barrier to entry is low, and there are many ways to contribute that do not require access to the latest technology. The result is a map made by local experts. OSM provides global map data in a unified tagging schema, although there are some local variations, this allows for consistency from country to country, for a truly global map.

<sup>&</sup>lt;sup>3</sup> https://welcome.openstreetmap.org/





## 3. Participatory Mapping

Participatory mapping a phrase commonly used in the OSM community. It is the creation of maps by local communities. They are visual representations of what a community perceives as its environment and the significant features within it. Participatory mapping is based on the premise that local communities possess expert knowledge of their surroundings.

Often this process is supported by organisations, with a target goal and funds to assist with the research and direction, depending on the purpose of the data creation. The emphasis, however, is always on providing skills for the community to create the maps themselves in order to represent the spatial knowledge of local citizens. Participatory mapping is at the core of HOT and their work, where local teams are the experts to create the necessary data in OSM.

This is also the case for both the remote digitisation of building footprints and the collection of detailed building information in the cities of Kathmandu and Dar es Salaam for the METEOR project. Kathmandu Living Labs (KLL) is a local company who has been involved with the OSM community for years, having worked on numerous projects with the Nepalese government. Ramani Huria is a community-based mapping initiative that began in Dar es Salaam training university students and local community members to create OSM maps of the most flood-prone areas of the city, in an effort to help combat the impact.





## 4. Remote Digitisation

## 4.1. Overview

Remote mapping is the process of modifying or adding new data to areas from a distance. In OSM this usually involves the use of a software program to trace information from satellite imagery or other earth observation material such as drone footage. All data in OSM is exposure data, as the type of information hosted relates to real objects, generally infrastructure and land use.

Once the data is mapped as vector data from aerial imagery, also known as raster data, this is uploaded to the OSM database, so that the results instantly form part of the global map data and is available to everyone. Using imagery to draw points, lines and shapes on the ground is also called 'digitising', and is generally done remotely. This means it does not have to physically be done in the same area.

Some people also call this process 'armchair mapping' because an individual can contribute without leaving their chair. The objective of remote mapping is to cover a large area quickly, obtaining a high-level overview of what is actually on the ground. It allows people to directly contribute to projects even if they cannot be physically present in the field.



In general, the first step for remote mapping in OSM is often identifying an area that needs to be mapped. Then it is important to determine if there is suitable imagery. A project can be created covering a certain area, the level of detail required should be specified, as well as the urgency. The work is then divided into sections by a gridded, known as tasks which can then be selected by individual remote mappers who each map a part of the overall area. This is checked by a second remote mapper who makes sure it is correct – a process called 'validation'. While there are many advantages to remote mapping, there are also some disadvantages. Data accuracy tends to be lower when users do not physically visit the places they are mapping, hence the emphasis on local mappers.





## 4.2. Tools

### 4.2.1. Tasking Manager

This tool was designed by HOT for collaborative mapping through the remote digitisation process in OSM, outlined in the previous section. The Tasking Manager divides up a project into smaller tasks that can be remotely digitised rapidly with many people working on the same overall area. This helps to avoid conflicts or duplication of people working on the same task. It shows which areas need to be mapped and which areas need to be validated. The tasks can then be selected and editing the OSM map can be done with the use of iD Editor, JOSM or another tool of preference.

→ C in https://tasks.hotosm.org		U I &
TASKING MANAGER Contribute Learn	About What is New?	English 🗸 Login
	a a Task for Pooplo in Nee	
IVIA	b a rask for reopie in Nee	
Join coordinated humanitarian free and editable map of the v	<ul> <li>mapping projects by taking a task and mapping a part of the wor world. Communities, organizations and governments worldwide ha</li> </ul>	ld in OpenStreetMap, the we access to these maps
to address local develop	ment challenges and aid disaster response. You can join thousand	Is of others to map
	Opensuleeuwap and support drese communities in need.	
	START MAPPING	
52	1,748,349	150,818
Mappers Online	Tasks Mapped	Total Mappers

#### Figure 2: HOT Tasking Manager

The Tasking Manager also allows monitoring of the overall progress and helps improve the consistency of mapping. It can be used either by an administrator who manages a project, or by mappers working to complete an area. The guidelines below briefly outline the steps for creating a project by a manager.

- 1. Open an internet browser, and go to the Tasking Manager at https://tasks.hotosm.org/
- 2. Log in using your OSM account click the *Login* button the top right corner, which will ask you to authorize access to your OSM account click *Grant Access*
- 3. Now that you have logged in click on the arrow next to your username and select *Create new project*
- **4.** Define your Area of Interest on the map, either by drawing it, importing a file, or using an OSM file; you should be familiar with the geographical area of the task





- 5. Choose Tasks Type either select a square grid or arbitrary tasks
- 6. Set Task Sizes split the area into larger or smaller tasks. You will need to decide an appropriate size, depending on the amount of features that need to be mapped
- 7. Trim Project cut the task grid to only the *Area of Interest*, this is optional
- 8. Review here you will be able to see what your project looks like and how many tasks you have created

Now you have created a project. Enter a detailed description and instructions and then publish

Reference	Link
Learn How to Use the Tasking	https://tasks.hotosm.org/learn
Manager	
OSM Tasking Manager Wiki	https://wiki.openstreetmap.org/wiki/OSM_Tasking_Manager

Table 4: Tasking Manager References

### 4.2.2. iD Editor

The iD Editor is a simple in-browser editor, allowing individuals to directly make changes in OSM. This is the editor beginner mappers are encouraged to use, as it is a user-friendly, making it easy to pick up the editing process of OSM. It also provides an initial walkthrough of the editor which is extremely helpful. This is the editor that is also used for quick additions or modifications of data, even by more advanced users who tend to use JOSM.







- 1. Open your Internet browser, and go to the OpenStreetMap website at http://www.openstreetmap.org
- 2. Log in using your OSM account click the *Login* button the top right corner
- **3.** Go to the place you want to edit either by entering the location in the search box, or by panning and zooming to the area you wish to edit. You can pan by holding the left mouse button and dragging the map to your desired area
- 4. Click on the small arrow next to *Edit* Then click *Edit with iD (in-browser editor)* 
  - For first-time users there will be a prompt for a walkthrough that begins inside the editor it is helpful practice for learning the basics, and learning new words and concepts (it is always accessible through the *Help*icon)
- 5. You can add **points**, for example, placing a well or latrine in your area entering in relevant known details. You can draw **lines**, for example adding a road that hasn't been drawn. Or you can draw **areas**, for example tracing a building that hasn't been digitized
- 6. Note: nothing will be uploaded to OSM until you click the *Save* button. Enter any comments about your edits, and if you are unsure about the data there is also the option "I would like someone to review my edits" for extra validation

Reference	Link
Learn iD Editor	https://learnosm.org/en/beginner/id-editor/
iD Editor Wiki	https://wiki.openstreetmap.org/wiki/ID

Table 5: iD Editor References

#### 4.2.3. JOSM

A feature-rich editor, JOSM, also known as the Java OpenStreetMap Editor is an open source desktop editor for OSM data. JOSM allows the user to create new data and edit existing data for OSM. The editor works offline, and makes it much easier for larger quantity and more detailed edits in a single sitting. While JOSM can be more intimidating to new users, the program is best suited for field operations and areas where internet is unreliable.







Figure 4: JOSM

1. Go to the following installation websites for both Java and JOSM:

#### https://java.com/en/download/

#### https://josm.openstreetmap.de/

- Once download and installation is complete, open JOSM. Connect JOSM to your OSM account to enable data uploads. To do so, access the preferences window by clicking the *Edit* menu and selecting *Preferences*. Click the *Connection Settings* sub-menu, enter your OSM credentials (username and password) and select Authenticate.
- **3.** Download data from OSM by clicking on the *Download* button and selecting an area of interest.
- 4. You can add aerial imagery as a background (if your internet connection is strong enough) by clicking on the *Imagery*menu and selecting an option such as *Bing*.
- 5. Just like in iD Editor, you can add points, lines, and areas using the add node tool. The difference is that these edits can be made while offline.
- 6. You should go through all data individually to check for spelling mistakes, incorrect tagging and geometries. To assist with the data cleaning process, you can use the validation tool, filters, and JOSM plugins including todo list.
- 7. When you're done, you can either save your work for later upload or for review, or immediately upload changes to OSM by clicking on the upload button.





**8.** Recommended: Have an experienced JOSM user serve as data quality manager, reviewing all data prior to upload.

Reference	Link
LearnOSM Getting Started with JOSM	https://learnosm.org/en/josm/start-josm/
JOSM Wiki Guide	https://wiki.openstreetmap.org/wiki/JOSM/Guide

Table 6: JOSM References

#### 4.3. Imagery

Aerial imagery is a term used to describe photographs that are taken from the sky. This can be done from airplanes, drones, helicopters, or even kites and balloons, but the most common source of imagery in terms of mapping comes from satellites orbiting the Earth. These photos can then be manipulated so that they can be used in Geographical Information Science (GIS) software.

One of the most basic questions to ask is what is the state of the available imagery? Is it up-to-date? If there has been a rapid evolution of the situation on the ground, for instance with the emergence of new buildings, new imagery needs to be obtained. If there is not satellite imagery available, does the host country have legislation allowing Unmanned Aerial Vehicles (UAVs), and what permissions are required?

The easiest starting point for finding imagery for digitisation in OSM is to check the imagery available in iD Editor. Simply click on **Background Settings** to see what imagery is available. The imagery available here is provided for free and is licensed. This generally includes satellite imagery from Bing<sup>4</sup>, DigitalGlobe<sup>5</sup>, ESRI<sup>6</sup> and Mapbox<sup>7</sup>. Sometimes the imagery available through OSM is not suitable for the project, as it may be out of date, has cloud coverage or the resolution is not high enough to distinguish individual buildings from one another.

This is when it would make sense to look at other sources of aerial imagery. You can start by using the Discover DigitalGlobe<sup>8</sup>, which is an online catalog service of satellite imagery. Another option is to either capture imagery with the use of a drone or by finding aerial imagery uploaded by others.

<sup>&</sup>lt;sup>4</sup> https://www.bing.com/maps/aerial

<sup>&</sup>lt;sup>5</sup> https://www.digitalglobe. com/

<sup>&</sup>lt;sup>6</sup> https://www.esri.com/en-us/arcgis/imagery-remote-sensing/content

<sup>&</sup>lt;sup>7</sup> https://www.mapbox.com/maps/satellite/

<sup>&</sup>lt;sup>8</sup> https://discover.digitalglobe.com





• • • A OpenAerialMap × +			
$\leftarrow$ $\rightarrow$ C $$ https://openaerialmap.org			ର୍ ୪ 💩 😂 🗄
OpenAerialMap	Expl	lore imagery Documentatior	1 About Blog
		A state	
The o	pen collection of aerial ima	igery.	
OpenAerialMap is a	n open service to provide access to a common	ns of openly licensed	
imagery and map laye	services. Download or contribute imagery to	the growing commons	
	of openly licensed imagery.		
	tart Exploring 💿 Watch the Vie	deo	
9,301	237	273	
Images	Sensors	Providers	

Figure 5: OpenAerialMap

OpenAerialMap (OAM) is a set of tools for searching, sharing, and using openly licensed satellite and UAV imagery. OAM offers a worldwide canvas on which various organizations can contribute to a patchwork of imagery. Open imagery can be critical for responding to crises and OAM makes it easy to host and access imagery for humanitarian response and development purposes, which is custom and up-to-date.

Reference	Link	
LearnOSM Aerial Imagery	http://learnosm.org/en/josm/aerial-imagery	
Discover by DigitalGlobe	https://discover.digitalglobe.com	
OpenAerialMap <u>https://map.openaerialmap.org</u>		
GEOSS Portal <u>http://www.geoportal.org</u>		
USGS Earth Explorer <u>https://earthexplorer.usgs.gov</u>		
Map Compare	https://tools.geofabrik.de/mc/	

Table 7: Aerial Imagery Resources





## 4.4. Quality Assurance

Quality assurance is a large part of any dataset and is true with OSM data. It is also known as the maintenance of a desired level of quality in a product. The higher quality your data is the more useful it is, so it is essential to manage the process along the way.

OSM is often more up-to-date and of a higher quality than other commercial maps in the least developed countries, but this requires mappers to be actively cleaning the data. While validation and quality control can be and should be performed at all stages of mapping, the main objective is to catch any mistakes in the data before uploading it to OSM or using it for any maps.

As there are many different possible workflows for data collection, there is no one way to perform validation and quality control. There are several tools that assist with this process while digitising in OSM, such as the 'Validator Tool' in JOSM. This helps highlight any errors in the data, such as intersecting geometries, unconnected nodes and missing tags, so that the mapper can correct them before uploading the data.



#### Figure 6: JOSM Validation Tool

Quality Assurance Wiki Page   https://wiki.openstre	reetmap.org/wiki/Quality_assurance

Table 8: Quality Assurance Resources





## 5. Kathmandu

## 5.1. Kathmandu Living Labs

Kathmandu Living Labs<sup>9</sup> (KLL) is a civic technology company, who aim to activate, inspire, and lead local communities using high impact technology to help transform societies. KLL creates the digital infrastructure so that government, nonprofits and businesses can use current tools to provide citizens with better services. KLL was formed in 2013 following a successful OpenDRI project with the World Bank, when the institution was registered as a non-profit civic technology company in Nepal.

Since their establishment, KLL have gone on to do numerous mapping initiatives including the National Housing Reconstruction Programme<sup>10</sup>, Secondary Cities<sup>11</sup>, QuakeMap.org<sup>12</sup>, Mapping and Opening Data for Local Governance and Citizen Engagement (MODEL4G) and a Structural Integrity and Damage Assessment project with the Department of Education in collaboration with the World Bank.

Using the KLL Collect SIDA application, data on the structural damage of 3,200 educational institutions was collected. This included over 10,000 buildings that were surveyed and the data validated. The collected data serves as a baseline for informing repairs, retrofitting and the reconstruction of the schools. Attribute information surveyed included the GPS coordinates of each school, number of pupils studying there, the different kinds and quantities of WASH facilities present, as well as the various risks associated with their infrastructure and surroundings

## 5.2. Homogeneous Zones

Kathmandu was divided into zones and classified by development patterns by the team at ImageCat. These homogeneous zones correspond to what the sensors should be able to detect, rather than who does what on the ground. ImageCat will then use these zones for an Artificial Intelligence (AI) module to capture the rest of the country. There are seven homogeneous zones identified in Kathmandu by ImageCat, this includes Dense Residential, High Urban, Industrial, Informal, New Industrial, Residential and Urban (Figure 7).

<sup>&</sup>lt;sup>9</sup> http://www.kathmandulivinglabs.org/

<sup>&</sup>lt;sup>10</sup> https://www.nepalhousingreconstruction.org/

<sup>&</sup>lt;sup>11</sup> https://secondarycities.state.gov/

<sup>12</sup> https://www.ushahidi.com/case-studies/quakemap





Figure 7: Kathmandu Homogeneous Zones

The geospatial dispersion of the homogenous zone display a concentration of urban settlement types towards the center of city, surrounded by dense residential, with industrial, new industrial and informal settlements scattered in between. The residential homogeneous zones are situated on the outskirts of the city. The total number of zones per homogenous type can be found in Table 9.

Homogenous Zone Type	No Zones Identified
Dense Residential	143
High Urban	23
Industrial	51
Informal	7
New Industrial	13
Residential	5
Urban	19
Total	261

Table 9: Kathmandu Homogeneous Zones





## 5.3. Tasking Manager Projects

KLL setup a project in the HOT Tasking Manager to carry out the remote digitisation of the building footprints found within the identified homogeneous zones in Kathmandu. The tool helps to coordinate and manage the large scale mapping of features required for the work package. The Tasking Manager project (Figure 8) was set up as private so that only the local KLL team could access the task for mapping. This was done due to the restrictions on the satellite imagery which was kindly provided by the United States Agency for International Development (USAID)<sup>13</sup>. The details of the imagery is covered in the following section.

(10) TASKING MANAGER	Contribute Learn	About What is New?		English 💙 mataharimhairi 🌱
MEDIUM 1- Active #5432 - MODE OBSERVATION EDIT PROJECT	Mappers LLING EXPOSU I ROUTINES: M	RE THROUGH EART ETEOR KATHMAND	Ч	SHARE
Download: Aol as .geojson, Ta	sks as .geojson, .osm, .gpx			
The escalating impacts of nati estimated that the world will increase in risk. Kathmandu L Geological Survey, ImageCat, Programme, focused on deve understanding of exposure to	ural hazards are caused mostly see the construction of 1 billio iving Labs is working together and the Global Earthquake Mo loping innovative applications help minimise these risks.	y by increasing exposure of populations a n new dwellings by 2050 and this growth with the Humanitarian OpenStreetMap T del on a UK Space Agency International P of earth observation (EO) technologies to	nd assets. It is may lead to rapid eam, British artnership improve	
METEOR aims to build and str order to better identify risk ar to apply data and assess haz suitability of purpose against information following the GEU buildings randomly selected to	engthen local and global resili d enable more effective decis rd exposure. The country-wid OSM data surveyed on the gro VAALL taxonomy developed as vithin homogenous zones by M	ence through complete, up-to-date, accur ion-making, through capacity-building of d datasets developed by ImageCat will be und within Kathmandu and Dar es Salaa part of the GFDRR Challenge Fund, will b athmandu Living Labs and Ramani Huria	ate exposure data in ocal decision makers tested for their n. Detailed attribute e collected for	
Status: Last updated: Priority: Completions	PUBLISHED 16 hours ago MEDIUM	Created by: Difficulty: Type(s) of mapping: Compaign:	Gauray Thapa BEGINNER BUILDINGS N/A	
Organisation: Mapper level required:	No	Campaign: Validator role required:	No	

<sup>&</sup>lt;sup>13</sup> https://www.usaid.gov/





Instructions	ACTIVITY AND STATS
Entities to map	
Buildings	
	Bodrysburdts
Changeset Comment	CAN PROPERTY IN THE
#hotosm-project-5432 #KLL #METEOR #digitizingkathmandu #HOT	and the second of the
Imagany	
https://magegeocenter.prg/mage/cest/sep/cest/Nepal 2018 63202 V2/ManServer/file/	the second second
(2)/(v)/(x)	
NO GO VI	
MAPPING: To get started with Mapping watch this video	
https://www.youtube.com/watch?v=rthnVpk08 VALIDATION: If you are working with	Notes And
validation watch this video https://www.youtube.com/watch?v=k-tVk7lePM You will be	Legend
using free satellite imagery to map roads. For a guideline on remote mapping please	Ready
теле история порагозналофилистрия врога наналофия спологофрафия.	Mapped
	Bad Imagery
	Validated
Ready to get started?	Invalidated
Contribute by mapping or validating work that has already been done.	Locked
MAP VALIDATE	Locked by you

#### Figure 8: Kathmandu Tasking Manager Project

The set up of the METEOR Kathmandu project in the Tasking Manager, follows the same layout as all projects. This includes a description of the projects and the mapping instructions, which detail the entities to map (buildings), the changeset comment (#KLL, #METEOR, #digitizingkathmandu #HOT), the imagery link (GeoCenter TMS) and instructions to get started.

No	Mapping Area	Project Link	Homogeneous Type
1	Kathmandu	https://tasks.hotosm.org/project/5432	Multiple

Table 10: Kathmandu Tasking Manager Project

### 5.4. Imagery

The imagery provided for the remote digitisation of building footprints within the homogeneous zones identified in Kathmandu was kindly provided by USAID in Nepal. It was provided through a Tile Map Service (TMS), which was hosted at their dedicated GeoCenter<sup>14</sup>. The satellite imagery was captured by the WorldView-4 sensor in December 2017, making it a little under a year old.

<sup>&</sup>lt;sup>14</sup> https://geocenterusaid.org/remotesensing/index.html





Ideally it would been better to have even more recent data, since there has been a fair amount of construction going on in Kathmandu following the 2015 earthquake. However, this was the best imagery dataset overall taking into account the high resolution, absence of cloud coverage and low off-nadir angle (22). Buildings that were potentially were not digitised from this dataset will be captured during the validation phase of mapping, when the footprint data is compared to other imagery datasets.



Figure 9: Digitised Buildings over Imagery in Bhaktapur Dense Residential Zone

Satellite Imagery Details	
Product	WorldView-4
Acquisition Date	30-12-2017
Off-Nadir	4.4
Cloud Coverage	0%
Resolution	30 cm

Table 11: Kathmandu Imagery Specifications





## 5.5. Statistics

Following the successful remote digitisation of all the footprints in OSM for the buildings located within the identified homogeneous zones, it can be seen that there is an overall increase in 33% of building stock (Table 12). This can be due to a number of factors, such as the development and building of new infrastructure across the city, as well as the fact that perhaps a lot of the buildings were not yet mapped in OSM. Although they have now been mapped for the purposes of the METEOR project, this data is freely available to everyone. Hopefully this data will be used for a variety of research and development initiatives that benefit the citizens of Kathmandu and Nepal.

	Building Count				
Homogeneous Zones	Before	After	Increase		
1 Residential	8,909	16,564	46%		
2 Dense Residential	71,310	104,945	32%		
3 Urban	8,829	10,671	17%		
4 Industrial	1,274	2,259	43%		
5 Informal	175	752	77%		
6 High Urban	595	749	21%		
7 New Industrial	510	675	24%		
Total	91,602	136,615	33%		

Table 12: Kathmandu Buildings Count Pre and Post Digitisation

Along with the increase in the quantity of building stock in OSM and the identified homogeneous zones in Kathmandu, it is also important that the quality of the data has also be improved. To assess the accuracy of the data, in particular the building footprints digitised, the team at KLL focused predominantly on geospatial errors such as intersecting geometries and nodes that are not connected. It is important to also check that the features have the required minimum tag of building=yes, so that the feature can be identified as a building in the OSM database. Once the team has gone on the ground to collect detailed information on that building, the tag will be changed to represent the functionality of the building, such as building=hospital.

There was a decrease of 0.18% in errors and a decrease of 5.46% in warnings of the building footprints, when comparing the final digitised data to the original data in OSM. These numbers were determined with the used of the *Validator Tool* in JOSM, which uses an algorithm to detect common errors found in OSM data. The detailed output errors and warnings from the Kathmandu analysis can be found in the Appendix.





Before					After				
Buildings	Error	Error (%)	Warning	Warning (%)	Buildings	Error	Error (%)	Warning	Warning (%)
91,602	174	0.19	7,214	7.88	136,615	14	0.01	3,308	2.42

Table 13: Kathmandu Building Quality Pre and Post Digitisation

### 5.6. Datasets

The exposure data created as part of WP4.2 was stored in OSM as vector data, as soon as the building footprints were digitised through the Tasking Manager. This data is created by tracing the building outlines on top of the satellite imagery provided by USAID, converting the raster data information into vector data, which can easily be used by other GIS software, including hazard impact models.

The final OSM building data will be shared with ImageCat as a Geopackage file, but it should also be noted that this data is available to anyone through OSM and can be downloaded using a variety of tools. The easiest tool to use is the HOT Export Tool, which allows a user to upload their area of interest as a GeoJSON file. This means that ImageCat or any other partner can simply upload the homogeneos zone file of their interest into the Export Tool and select the building tag, to easily extract all the building footprints along with their attribute data for download, into a number of various file formats, such as Geopackages, Shapefiles and PBFs.

A couple of the Kathmandu homogeneous zones and their final OSM buildings footprints can be seen below. This includes the Namuna Chowk, which was identified as a dense residential (Figure 10). The Chhuani industrial zone (Figure 11), the informal settlement zone in Thapathali (Figure 12), the new industrial zone in Maitighar (Figure 13) and the urban zone in Balaju Machhapokhari (Figure 14). These provide a brief overview of the building patterns per development types as identified by the homogenous zones of ImageCat.





Figure 10: Kathmandu Dense Residential Zone



Figure 11: Kathmandu Industrial Zone





Figure 12: Kathmandu Informal Zone



Figure 13: Kathmandu New industrial Zone







Figure 14: Kathmandu Urban Zone

## 6. Dar es Salaam

## 6.1. Ramani Huria

Ramani Huria<sup>15</sup> is a community-based mapping initiative that began in Dar es Salaam, Tanzania, training university students and local community members to create OSM maps of the most floodprone areas of the city. This was the result of a collaboration with the Tanzanian Commission of Science and Technology (COSTECH), the Government of Tanzania, the City Council of Dar es Salaam, University of Dar es Salaam and Ardhi University, supported by HOT, the Red Cross and the World Bank.

To date, Ramani Huria has trained over 450 community mappers, while mapping 26 wards, 1,254 kilometers of waterways, 3,396 kilometers of road networks and 949,655 building footprints. The impact of the initiative and the power of community mappers was evident when an additional 443,347 buildings were added in OpenStreetMap for the city of Dar es Salaam in the space of 6 months, between August and December 2017.

<sup>&</sup>lt;sup>15</sup> http://ramanihuria.org





The Ramani Huria initiative really put Dar es Salaam onto the map, which is home to approximately 1.3 million residents. As the map evolved over time, the benefits have multiplied as they are now serving as foundational tools for development within all socio-economic spheres beyond flood resilience, such as include health care services, which are key to reducing illnesses and mortality during flooding events, as well as toilets, water sources, and building infrastructure.

### 6.2. Homogeneous Zones

There are six homogeneous zones of development patterns identified across Dar es Salaam by ImageCat. These include high urban development, industrial development, natural forest land, rural settlement, single family residential and urban development. The geospatial spread of these zones are much more scattered and sparse compared to the zones identified in Kathmandu, with some high urban development zones located in the center and towards the northwest of Dar es Salaam. Industrial development zones are also located in the center, as well as towards the west of the city. Zones of natural forest land are located on the outskirts of the cities as expected, same as the rural settlements. Single family residential zones are scattered throughout the city, with the urban development following a similar geospatial pattern as the high urban development zones in the city center and towards the northwest (Figure 15).



Figure 15: Dar es Salaam Homogeneous Zones





Homogeneous Zone Type	No Zones Identified
High Urban Development	3
Industrial Development	3
Natural Forest Land	3
Rural Settlement	4
Single Family Residential	11
Urban Development	7
Total	31

Table 14: Dar es Salaam Homogeneous Zones

## 6.3. Tasking Manager Projects

The projects in the Tasking Manager for the remote digitisation of building footprints in Dar es Salaam, were set up a little differently than they were for Kathmandu. Although the project pages have the same standard Tasking Manager layout, with the project description and mapping instructions (Figure 16), it is the number of projects created that differ. Where as KLL chose to use a single project to map all of the homogeneous zones, the Ramani Huria team chose to split their mapping across 14 Tasking Manager projects (Table 15).

There is no recommended way how this should be done, and generally this is left up to the local team to decide, so that they can select the method most effective for their mapping process. One of the reasons a team may choose to have multiple Tasking Manager projects as opposed to a single one, is the ability to divide the tasks to separate mapping teams for ownership.

This is particularly useful if the team conducting the remote digitisation of the building footprints within certain projects, will also be responsible for the data collection on the ground for the attribute information. This is because the Tasking Manager is also an effective tool for the coordination and monitoring of mapping efforts on the ground, as the projects area of interest can be identified and pulled into other HOT tools such as OSM Analytics<sup>16</sup>, MapCampaigner<sup>17</sup> and the Export Tool<sup>18</sup>. These tools will be covered in detail during the ground data collection portion of the work package.

<sup>&</sup>lt;sup>16</sup> https://osm-analytics.org

<sup>&</sup>lt;sup>17</sup> https://campaigns.hotosm.org/

<sup>&</sup>lt;sup>18</sup> https://export.hotosm.org/





TASKING MAN	AGER Contribute Learn	About What is New?		English 💙 mataharimhairi 🗸
MEDIUM 0- Ac #5370 - Pwa	tive Mappers			SHARE
EDIT PROJECT	l			
Download: Aol as .geojs	on, Tasks as .geojson, .osm, .gpx			
The METEOR project is f ImageCat, National Soci Minister's Office) of Tan (OPM).	unded by the UK Space Agency and is any for Earthquake Technology (NSET) rania, the Humanitarian OpenStreetM	comprised of GEM, the British Geolo The Disaster Management Departm ap Team (HOT) and Oxford Policy Ma	gical Survey (BGS), ent (OMD - Prime inagement Limited	
The main objective of th built environment to nat their differing exposure Understanding disaster	e project is to develop and deliver mo ural hazards in developing countries. and hazard types. The project addres risk, with a specific aim to reach all 48	re accurate levels of the exposure of The first pilot countries are Nepal ar ses Priority 1 of the Sendai Framewo Least Developed ODA (Official Deve	populations and the d Tanzania, because of rk for DRR: iopment Assistance).	
TZMETEO	R			
Status; Last updated: Priority:	PUBLISHED a month ago MEDIUM	Created by: Difficulty: Type(s) of mapping:	dorica_mugusi ADVANCED ROADS   BUILDINGS   WATERWAYS   LAND_USE	
Organisation: Mapper level required:	#OMDTZ Yes	Campaign: Validator role required:	OTHER #METEOR No	
Instructions Map Instructions Entities to map Buildings	Validate Questions and Com	ments		ACTIVITY AND STATS
Changeset Comment #hotosm-project-5370		Z	Y.	X-X
Please do not delete any e	isting buildings with metadata	Ly.		the start is
If there is a building that al of replacing it (or at least o	ready has tags but is badly digitized, pleas opy over the tags).	e repair it instead		
Once buildings are done. I' watercourses, and other fe repair everything else. In p according to the Data Mod	d also like to ensure that all other digitiza atures) is also done properly. Buildings ci articular, please ensure that all roads are el.	tion (roads, yme first, but then property classified		
Ready to get s Contribute by mappin	tarted? g or validating work that has already bee	a done.	red magery ited	Bing Imagery     Population density
МАР	VALIDATE	Locke	d by you	MapBox Aerial     OpenStreetMap     CopenStreetMap contributors

Figure 16: Dar es Salaam Tasking Manager Project





No	Mapping Area	Project Link	Homogenous Type
1	Dar Wards	https://tasks.hotosm.org/project/5371	Multiple
2	Pwani	https://tasks.hotosm.org/project/5370	Rural Settlement
3	Pwani II	https://tasks.hotosm.org/project/5395	Natural Forest Land
4	Gerezani	https://tasks.hotosm.org/project/5386	Urban Development
5	Kagera Mikoroshoni	https://tasks.hotosm.org/project/5387	Single Family Residential
6	Karakata	https://tasks.hotosm.org/project/5389	Single Family Residential
7	Kisutu	https://tasks.hotosm.org/project/5390	High Urban Development
8	Kivule	https://tasks.hotosm.org/project/5391	Rural Settlement
9	Miembeni	https://tasks.hotosm.org/project/5392	Industrial Development
10	Mtakuja	https://tasks.hotosm.org/project/5394	Single Family Residential
11	Sinza	https://tasks.hotosm.org/project/5396	Single Family Residential
12	TPDC	https://tasks.hotosm.org/project/5397	Single Family Residential
13	Ungindoni	https://tasks.hotosm.org/project/5398	Rural Settlement
14	Keko Magurubasi	https://tasks.hotosm.org/project/5405	Single Family Residential

Table 15: Dar es Salaam Tasking Manager Projects

#### 6.4. Imagery

The imagery used for the remote digitisation of the building footprints within the homogeneous zones of Dar es Salaam was provided by the consulting firm COWI<sup>19</sup>. The data was acquired by a piloted fixedwing aircraft, commissioned by the Tanzanian Ministry of Lands<sup>20</sup> and the World Bank<sup>21</sup>. This imagery was provided to Ramani Huria for use on several of their projects focused on the mapping of infrastructure in Dar es Salaam. Although the data is almost 2 years out of date, it is still the best imagery available for digitisation at 10 cm resolution. The Tanzanian government are currently planning to re-digitise the entire city with the imagery.

Piloted Imagery Details	
Product	COWI
Acquisition Date	2016
Off-Nadir	0
Cloud Coverage	0%
Resolution	10 cm

Table 16: Dar es Salaam Imagery Specifications

<sup>&</sup>lt;sup>19</sup> https://www.cowi.com/

<sup>&</sup>lt;sup>20</sup> https://www.tanzania.go.tz/

<sup>&</sup>lt;sup>21</sup> https://www.worldbank.org/







Figure 17: Satellite Imagery, Dar es Salaam Industrial Zone



Figure 18: Satellite Imagery with Digitised Buildings, Dar es Salaam Industrial Zone





## 6.5. Statistics

Looking at the final numbers of the digitised building footprints in OSM within the homogeneous zones of Dar es Salaam, it can be seen that there is an overall increase in 26% of building stock (Table 17). This is slightly lower compared to the 33% increase in Kathmandu, which can be attributed to the large digitisation efforts of Ramani Huria in 2017 to map a large extent of the city. Although the overall building stock number did not increase greatly, the quality of the building footprints were greatly enhanced with the use of the 10 cm resolution imagery for digitising.

Homogeneous Zones	Building Count			
	Before	After	Increase	
1 High Urban Development	331	443	25%	
2 Industrial Development	418	489	15%	
3 Natural Forest Land	0	0	0%	
4 Rural Settlement	790	1767	55%	
5 Single Family Residential	3939	4923	20%	
6 Urban Development	1167	1416	18%	
Total	6,645	9,038	26%	

Table 17: Dar es Salaam Building Count Pre and Post Digitisation

While comparing the quality of the building footprints pre and post digitising for the METEOR project in OSM, there were several factors highlighted. This includes the increased accuracy of building alignment, building shape and the inclusion of absent buildings.

The alignment of numerous building footprints were noticeably off in the older OSM data, most likely due to the use of multiple imagery sources. The re-digitisation of these footprints with the 10 cm resolution imagery allowed for all the buildings located within the homogeneous zones to be properly aligned. Similarly, with the older OSM data, most building shapes were inaccurate due to the use of poor resolution imagery used for digitisation as this makes the outline of the buildings hard to detect. With the COWI imagery, the buildings can be seen clearly and the building footprints clearly defined. Finally, one of the biggest issues with the use of poor imagery for digitising in OSM, is how easy it is to completely miss features.

When the resolution is poor, or there is cloud coverage in the imagery, it greatly reduces the ability to detect buildings. Since the imagery had a resolution of 10 cm and zero cloud cover, it enabled the Ramani Huria team to detect buildings that were potentially missed during the last phase of digitisation, as well as pick up new buildings.







Figure 19: Dar es Salaam OpenStreetMap Buildings Pre Digitisation



Figure 20: OpenStreetMap Buildings Post Digitisation, Dar es Salaam





## 6.6. Datasets

The OSM building stock in some of the homogenous zones in Dar es Salaam help to demonstrate the geospatial layout of the development patterns. Maps of the high urban development zone in Kisutus, as well as the industrial development zone in Kurasini, the rural settlement zone in Kisarawe, the single family residential zone in Karera Mikoroshoni and the urban development zone in Gerezani.

The full dataset of the digitised building footprints will be shared directly with ImageCat as Geopackage file. Same as the Kathmandu exposure data, this geospatial vector information is hosted in OSM, and can be extracted with the use of the HOT Export Tool. These downloads have already been set up and can be accessed through the following links:

Kathmandu | <a href="https://export.hotosm.org/en/v3/exports/bf3c20c6-dc0e-423a-a9b9-97b53cd7a8da">https://export.hotosm.org/en/v3/exports/bf3c20c6-dc0e-423a-a9b9-97b53cd7a8da</a>Dar es Salaam | <a href="https://export.hotosm.org/en/v3/exports/841859fc-4e3e-4f13-95f9-787ee868786f">https://export.hotosm.org/en/v3/exports/bf3c20c6-dc0e-423a-a9b9-97b53cd7a8da</a>



\* Please note that these links will become inactive after 3 months from December 1, 2018

Figure 21: Dar es Salaam High Urban Development Zone





Figure 22: Dar es Salaam Industrial Development Zone



Figure 23: Dar es Salaam Rural Settlement Zone





Figure 24: Dar es Salaam Single Family Residential Zone



Figure 25: Dar es Salaam Urban Development Zone





## 7. Conclusion

The successful mapping of building exposure data in OSM with the use of EO data can be attributed to the amazing teams in both Kathmandu and Dar es Salaam. KLL put together a team of students from Pokhara and partnered with Paschimanchal Campus Institute of Engineering, who kindly provided them with the space to run the mapping 'camp'. Check out the blog by the KLL team to read more about their experiences during the remote digitisation portion of the project. Similarly the team in Dar es Salaam was a mixture of Ramani Huria members and students from the University of Dar es Salaam and Ardhi University to carry out the mapping.

### Kathmandu Living Labs

https://www.hotosm.org/updates/kathmandu-from-above/



Figure 26: Kathmandu Living Labs Digitisation Team

#### Ramani Huria

https://www.hotosm.org/updates/building-disaster-resilient-countries-slash-cities-through-open-spatial-data-and-exposure-analysis/



Figure 27: Ramani Huria Digitisation Team





# Appendix 1

Pre Digitisation

Errors (174)
Building duplicated nodes (87)
Duplicated relations (1)
Duplicated ways (19)
Highway duplicated nodes (4)
Landuse duplicated nodes (4)
Multipolygon is not closed (2)
Opening hours syntax (14)
relation without type (11)
Role verification problem (13)
wrong value: area=apartment, use area=yes or area=no instead (1)
wrong value: area=college, use area=yes or area=no instead (3)
wrong value: area=school, use area=yes or area=no instead (15)

Warnings (7,214)
access=designated' is meaningless, use more specific tags, e.g. 'bicycle=designated' (1)
addr:street with multiple values (11)
amenity inside amenity (30)
amenity node connected to a highway (10)
area=yes on a node. Should be drawn as an area. (5)
Area style on outer way (5)
Barrier entrance not set on a barrier (2)
building:levels should have numbers only with optional .5 increments (5)
building node connected to a highway (1)
deprecated tagging (65)
ele must be a numeric value, in meters and without units (1)
Email validator (4)
House number without street (2,497)
Invalid white space in property key (2,717)
isolated node which must be connected to a way (15)
key with uncommon character (4)
landuse=cemetery on a node. Should be drawn as an area. (1)
leisure=park on a node. Should be drawn as an area. (4)
leisure inside leisure (4)
leisure node connected to a highway (1)
missing tag (385)
Misspelled property key - Key 'aminity' looks like 'amenity'. (4)
Misspelled property value (9)
name with multiple values (12)
natural=beach on a node. Should be drawn as an area. (1)
natural=water on a node. Should be drawn as an area. (1)





Node connects a power line or cable with an object which is not related to the power infrastructure. (7)
node connects highway and building (104)
Nodes at same position (36)
Nodes duplicating parent way tags (7)
Non-Way in multipolygon (3)
No outer way for multipolygon (1)
office node connected to a highway (1)
Opening hours syntax (383)
Other duplicated nodes (32)
Overlapping Identical Landuses (2)
Overlapping ways (77)
place=yes is unspecific. Please replace 'yes' by a specific value. (4)
Property values contain multiple white spaces (42)
Property values start or end with white space (45)
Relations with same members (1)
Relation type is unknown (60)
Role verification problem (51)
Route scheme is unspecified. Add public_transport:version (2=public_transport; 1=legacy) (35)
Same value of addr:housenumber and addr:housename (2)
shop inside shop (4)
shop node connected to a highway (11)
suspicious tag combination (9)
Tags with empty values (2)
Tag value contains character with code less than 0x20 (8)
tourism inside tourism - tourism=hotel inside tourism=hotel (9)
Unclosed way (3)
Unconnected nodes without physical tags (149)
unnecessary tag (97)
Unspecific highway type (25)
Untagged ways (commented) (118)
unusual value of direction (4)
unusual value of height: meters is default; point is decimal separator; if units, put space then unit (1)
unusual value of width: meters is default; point is decimal separator; if units, put space then unit (2)
URL validator (11)
Value of 'footway' should either be 'sidewalk' or 'crossing'. For sidewalks use 'sidewalk=left right both no'
instead. (1)
waterway=ditch is the tag for the linear waterway. To tag the water area use natural=water + water=*
instead. (1)
Waterway ends without a connection to another waterway or the direction of the waterway is wrong. (1)
Way end node near other highway (22)
Ways with same position (38)
Way terminates on Area (8)
Wrong highway tag on a node (2)





## Post Digitisation

Frors (14)	
Role verification problem (14)	

Warnings (3,308)
access=designated' is meaningless, use more specific tags, e.g. 'bicycle=designated' (1)
addr:street with multiple values (11)
area=yes on a node. Should be drawn as an area. (5)
Area style on outer way (5)
Area style way is not closed (3)
building:levels should have numbers only with optional .5 increments (5)
ele must be a numeric value, in meters and without units (1)
Email validator (3)
House number without street (2,466)
isolated node which must be connected to a way (17)
key with uncommon character – infrastructure facility (1)
landuse=cemetery on a node. Should be drawn as an area. (1)
leisure=park on a node. Should be drawn as an area. (4)
leisure inside leisure (3)
name with multiple values (11)
natural=beach on a node. Should be drawn as an area. (1)
natural=water on a node. Should be drawn as an area. (1)
Node connects a power line or cable with an object which is not related to the power infrastructure. (3)
node connects highway and building (76)
Nodes at same position (28)
Nodes duplicating parent way tags (7)
Non-Way in multipolygon (4)
No outer way for multipolygon (1)
office node connected to a highway (1)
Opening hours syntax (3)
Overlapping ways (45)
payment:credit_cards=yes is inaccurate, use payment:mastercard=yes or payment:visa=yes or instead (3)
place=yes is unspecific. Please replace 'yes' by a specific value. (4)
Relations with same members (1)
Relation type is unknown (60)
Role verification problem (49)
Route scheme is unspecified. Add public_transport:version (2=public_transport; 1=legacy) (35)
Same value of addr:housenumber and addr:housename (1)
Self-crossing ways (2)
shop inside shop (3)
shop node connected to a highway (7)
suspicious tag combination (15)
Tag value contains character with code less than 0x20 (6)
tourism inside tourism - tourism=hotel inside tourism=hotel (9)
Unclosed way (3)





Unconnected nodes without physical tags – Has tag containing 'fixme' or 'FIXME' (3) Unspecific highway type (18) unusual value of direction (4) unusual value of height: meters is default; point is decimal separator; if units, put space then unit (1) unusual value of width: meters is default; point is decimal separator; if units, put space then unit (2) URL validator (12) Value of 'footway' should either be 'sidewalk' or 'crossing'. For sidewalks use 'sidewalk=left|right|both|no' instead. (1) waterway=ditch is the tag for the linear waterway. To tag the water area use natural=water + water=\* instead. (1) Waterway ends without a connection to another waterway or the direction of the waterway is wrong. (1) Way end node near other highway (65) Ways with same position (32) Way terminates on Area (2)

Wrong highway tag on a node (3)